

Network Interface Cards

PRODUCT INFORMATION

Allied Telesis™

2911 Series

PCI EXPRESS GIGABIT NETWORK INTERFACE CARDS



Allied Telesis 2911 Series Network Interface Cards feature a PCI Express (PCIe x1) design, providing the maximum possible bandwidth and bus efficiency while providing the benefits of low power consumption.

High Reliability

The 2911 Series Gigabit interface comes with a comprehensive Microsoft Windows utility which performs detailed tests, diagnostics and analysis.

Advanced Manageability

The priority queuing offered by the 2911 Series can help users set up the network based on their own needs. The comprehensive diagnostics and configuration software suite provides system administrators and engineers with a profound tool to analyze the adapter card and check specific data.

Key Features

Management Software

- » VLAN support
- » Link aggregation LACP
- » Link aggregation smart switch
- » Failover

Advanced Properties

- » Jumbo frames
- » Checksum offloading
- » Secure transmissions
- » PCI Express (PCIe x 1)
- » Smart Load Balancing (SLB) and failover

- » Link aggregation (IEEE 802.3ad)
- » Generic trunking (FEC/GEC) / IEEE 802.3ad-draft static
- » SLB (auto-fallback disable)
- » iSCSI boot support
- » UEFI network boot available upon request
- » IEEE 802.1x flow control
- » IEEE 802.3az Energy-Efficient Ethernet
- » CPU task offload
- » TCP segmentation
- » SNMP

- » IPv6
- » MSI and MSI-X capabilities (up to 17 MSI vectors)
- » Receive Side Scaling (RSS)
- » Transmit Side Scaling (TSS)
- » I/O virtualization support for VMWare, NetQueue and Microsoft VMQ
- » 17 receive queues and 16 transmit queues
- » Low-profile and standard height brackets included
- » Windows XP, Vista, 7, 8, and Linux

Specifications

Management Features

Windows Management Instrumentation (WMI)
PXE 2.1
SNMP
PCI Express v2.0

Bus Type

PCIe x1

Ethernet

IEEE 802.1p	Quality of Service
IEEE 802.1Q	VLANs
IEEE 802.2	LLC
IEEE 802.3ac	MAC
IEEE 802.3az	Energy-Efficient Ethernet
IEEE 802.3x	Flow control auto-negotiation
IEEE 802.3z	1000 Base-X
IEEE 802.3ad	Link aggregation
IEEE 802.3ab	10/100/100T

Drivers

Windows 8, 64- or 32-bit
Windows 7, 64- or 32-bit
Windows Vista, 64- or 32-bit
Windows XP, 64- or 32-bit
Windows Server 2012 R2, 64-bit
Windows Server 2012, 64-bit
Windows Server 2008 R2, 64- or 32-bit
Windows Server 2008, 64- or 32-bit
Windows Server 2003, 64- or 32-bit
Linux 2.6

Interface Type and Connectors

1000SX/SC connector	
Optical sensitivity	-17 dBm
Output optical power	-9.5/-4 dBm
Wavelength	850 nm

1000SX/LC connector	
Optical sensitivity	-17 dBm
Output optical power	-9.5/-4 dBm
Wavelength	850 nm

1000LX/SC connector	
Optical sensitivity	-20 dBm
Output optical power	-9/-3 dBm
Wavelength	1310 nm

1000LX/LC connector	
Optical sensitivity	-20 dBm
Output optical power	-9/-4 dBm
Wavelength	1310 nm

Status Indicators

LED	On	Link up
	Off	Link down
	Blinking	Activity

Power

Power consumption	1.51 to 2.42W (varies by model)
Signaling voltage	3.3V

Environmental Specifications

Operating temperature	0°C to 40°C (32°F to 104°F)
Relative humidity	5% to 90% (non-condensing)
Storage temperature	-25°C to 70°C (-13°F to 158°F)

Physical Characteristics

Dimensions (W x H)	8.8 cm x 6.9 cm (3.5 in x 2.7 in)
Weight	.068 kg (.13 lb)

Compliance

RoHS
UL
FCC/EN55022 Class A
TUV
EN55024
CE
C-TICK
VCCI

Ordering Information

Single Port Models

AT-2911SX/SC-xxx
1000SX SC PCI Express x1 adapter card

AT-2911SX/LC-xxx
1000SX LC PCI Express x1 adapter card

AT-2911LX/SC-xxx
10 km, 1000LX SC PCI Express x1 adapter card

AT-2911LX/LC-xxx
10 km, 1000LX LC PCI Express x1 adapter card

AT-2911SFP-xxx
1G SFP PCI Express x1 adapter card

Dual Port Models

AT-2911STX/SC-xxx
1000SX (SC) + 10/100/1000T PCI Express x1 adapter card

AT-2911STX/LC-xxx
1000SX (LC) + 10/100/1000T PCI Express x1 adapter card

AT-2911LTX/SC-xxx
10 km, 1000LX (SC) + 10/100/1000T PCI Express x1 adapter card

AT-2911LTX/LC-xxx
10 km, 1000LX (LC) + 10/100/1000T PCI Express x1 adapter card

AT-2911ISX/2LC-xxx
1000SX x 2 LC PCI Express x1 adapter card

AT-2911ILX/2LC-xxx
10 km, 1000SX x 2 LC PCI Express x1 adapter card

AT-2911SFP/2-xxx
1G SFP x 2 PCI Express x1 adapter card

AT-2911T/2-xxx
100 m, 10/100/1000T x 2 PCI Express x1 adapter card

Where xxx = 001 for single pack
901 for single pack, Federal and Government

Ships with low-profile bracket attached to adapter card.
Standard bracket is included in packaging.



Americas Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895
Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830
EMEA & CSA Operations | Incheonweg 7 | I437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

alliedtelesis.com

© 2014 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000511 Rev. A